

"EXPRESS MAIL" CERTIFICATE

EXPRESS MAIL NUMBER: EL69547516405
DATE OF DEPOSIT 6/29/01

I hereby certify that this paper or fee is being deposited with the United States Postal Service - "Express Mail Post Office To Addressee" Service under 37 CFR 1.10 on the above indicated date and is addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231



Tameka Watt

Atty Dkt: **GREN001**

APPLICATION

FOR

UNITED STATES LETTERS PATENT

ENTITLED:

POLO TRAINING APPARATUS

APPLICANTS: William Ronald Greenwood
Residency: Chester, UK
(citizen of The United Kingdom)

1066790" 65096860

DESCRIPTIONPOLO TRAINING APPARATUS

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100

At present, the opportunities for practising polo other than in a polo match are limited. One option is for a player to ride a polo pony and to hit a series of series of balls across a field. Whilst such practice is very effective, it is a relatively expensive option and requires the use of a large area. Moreover, there is a problem with positioning the practice balls and in retrieving them once they have been hit.

The second option is for a player to sit astride a dummy horse and to hit a series of balls located on the floor. Whilst this can be done in a much smaller area, the fact that the dummy horse is stationary means that relatively few balls can be lined up ready to be hit. Moreover, the practice which this option affords is not particularly realistic.

It is an object of the present invention to provide a polo training apparatus which overcomes or alleviates the problems associated with the prior art.

In accordance with a first aspect of the present invention, a polo training apparatus comprises a dummy horse and at least one ball-locating surface located adjacent to and below the dummy horse, the ball-receiving surface being displaceable relative to the dummy horse.

Preferably, the or each ball-receiving surface is located to one side of the dummy horse and preferably is arranged to move in a direction parallel to the fore/aft direction of the dummy horse.

In this way, a ball located on the ball-receiving surface will be displaced relative to the dummy horse, thereby simulating the movement of the horse

relative to the ground and to the ball.

Preferably, the apparatus comprises a plurality of displaceable ball-receiving surfaces.

In a preferred embodiment, a ball-receiving surface is provided on each side of the dummy horse.

Preferably, the or each movable surface comprises an endless conveyor belt.

In one preferred embodiment, the dummy horse is itself displaceable, e.g. reciprocable, preferably to simulate the action of a moving horse. Preferably, the speed of the horse is linked to the speed of the or each ball-receiving surface, whereby an increase in the speed of one increases the speed of the other. In this way, a very realistic action can be achieved in which the induced motion of the dummy horse corresponds with an increased speed of the ball-receiving surface.

Preferably, the dummy horse and the or each moving surface are displaced by the same means, e.g. an electric motor.

The apparatus may further comprise one or more inclined surfaces adjacent to the or each moving surface, whereby a ball which has been hit off the moving surface is encouraged to return to the surface, where it can be hit again. The apparatus may further comprise a peripheral enclosure, e.g. a cage or net, to prevent balls from inadvertently being hit out of the apparatus.

In accordance with a second aspect of the present invention, a polo training apparatus comprises a dummy horse having a substantially rigid frame and a body portion pivotally mounted on the frame, whereby the body portion can be

FOCUS 90" 5535850

pivoted from side to side.

The side to side pivoting of the body portion of the dummy horse simulates more closely the movement of a rider and horse as a ball is hit.

Preferably, the body portion is biased (e.g. by means of springs) whereby the body portion can be displaced to either side against a restoring force. In one embodiment, the apparatus further comprises a sensor adapted to detect pressure from one or more parts of the rider's body. For example, the apparatus may comprise a sensor to detect pressure applied by one or both knees or feet of the rider. There may also be display means, e.g. a light, which indicates to a rider when correct pressure is applied, and therefore the correct posture is assumed, for a particular shot.

In accordance with a third aspect of the present invention, a horse riding training apparatus comprises a movable body portion upon which a rider sits and means for displacing the body portion, the apparatus further comprising sensor means responsive to a simulated riding action in order to control the apparatus.

In one embodiment, the apparatus comprises pressure sensors adapted to respond to pressure from a particular part of the rider's body, for example the rider's feet, knees or hand. In this way, the apparatus can be arranged such that application of a sharp pressure to sensors on either side of the body results in commencement of the movement of the body portion and further application of pressure to those areas causes an increase in the speed of movement of the body portion.

In one embodiment, the apparatus further comprises a simulated horse head portion, reins extending from the horse head portion and a control means

00896059 052904

actuated by movement of the head with the reins.

For example, movement of the head may be arranged to actuate a switch which causes the motion of the horse to slow or stop.

By way of example only, a specific embodiment of the present invention will now be described, with reference to the accompanying drawings, in which:-

Fig. 1 is a perspective view, partly cut-away, of an embodiment of polo training apparatus in accordance with the present invention;

Fig. 2 is a plan view of a portion of the apparatus illustrated in Fig. 1;

Fig. 3 is a side view, partly cut-away, of a portion of the apparatus of Fig. 1;

Fig. 4 is a transverse cross-section through a portion of the apparatus shown in Fig. 1; and

Fig. 5 is a side view, partly cut-away, of a head portion of the apparatus shown in Fig. 1.

Referring firstly to Fig. 1, a polo training apparatus comprises a simulated polo pony 10 (hereinafter referred to as a "dummy horse") located on a base B within an enclosure defined by two end walls 12, 14 and two side walls 16, 18, all of netting or wire mesh. The dummy horse 10 is mounted on a frame 40 (Fig. 3) which is normally surrounded by enclosing walls 20. Conveyor belts 22, 24 are provided one on each side of, and below, the dummy horse, with the upper run of each conveyor generally horizontal and with the direction of motion of the conveyor belts being in the fore/aft direction of the dummy horse, as indicated by arrows M.

106290" 55896880

Immediately laterally outwardly of the conveyor belts 22, 24 are located upwardly inclined front, rear and side walls 26, 28, 30, 32. A generally horizontal wall 34 is also provided at the top of the rear inclined wall 32.

Two targets 36 are provided on the front wall 12, one to each side of the dummy horse 10. Similar targets 36 are provided on the rear wall 14 and one each on the side walls 16, 18. The targets comprise a pressure-sensitive area at their centre, which is actuated by the impact of a ball, generating a signal. A counter 38 is also provided on the front wall, to count the number of "hits" on the targets 36, as will be explained.

Referring to Figs. 2 to 4, the dummy horse is supported on a fixed metal frame which is mounted on a fixed base wall B. As mentioned earlier, the fixed frame 40 is normally surrounded by enclosing walls 20, but these have been omitted from Fig. 3. A movable frame 42 is movably mounted on the fixed frame 40, as will be explained, and a simulated horse body 44 is mounted on the movable frame 42. A pivotally mounted neck portion 46 extends from the front of the body portion 44 and a pivotally mounted head 48 projects from the distal end of the neck portion 46. The head portion 48 is mounted to the neck portion such that the head pivots in the opposite direction to the neck portion, in the manner described in GB 2,256,597.

The frame 42 and the body portion 44 mounted thereon is displaceable with respect to the fixed frame 40 by means of a motor M mounted on the fixed frame portion. The operation of the motor is under the control of an electronic control unit 50. An eccentric drive 52 is mounted to the output of the motor M which in turn is connected to the movable frame portion 42 via a rigid arm 54 which is

170
25
a p

t of the motor 50 is also fixed to the belt and pulley arrangement. The rollers 68 around each of which the belt is trained. Thus, operation of the motor 50 causes motion in the horse but also causes rotation of the speed of the motor 50 and the speed of the conveyor.

With reference to Fig. 4, it will also be noted that the horse body 40 is pivotally mounted with respect to the movable frame 42 such that the body 40 can pivot from side to side. The body portion is biased to a central position by means of restoring springs 70, 72 connecting the body portion 44 and the frame 42.

As best seen in Fig. 5, reins 74 extend from the head portion 48 of the horse, whereby the head portion can be pivoted downwardly with respect to the neck portion. A rod 76 extends between, and is pivotally mounted to, the head portion 48 and the neck portion 46 and is provided with two rings 78 which, as the head portion is pivotally mounted by means of the reins, actuates a microswitch 80 whose output is connected to the electronic control unit 50 and which is adapted to slow down or, optionally, stop the apparatus.

In order to operate the apparatus the rider kicks the two feet sensors 82 simultaneously, which produces a signal causing the control apparatus 50 to start the motor M. Alternatively the faster control button 90 may be depressed or the upper sensor 86 on the neck portion may be pushed. Operation of the motor M induces a simulated galloping motion of the horse body and simultaneously operates the conveyor belts 22, 24, as described previously. Further simultaneous kicking of the feet sensors 82 (or depression of the faster control button 92 or pushing of the sensor 86) causes an increase in the speed of the motor M. When the motor M is rotating at the desired speed (as indicated by the LCD speed display panel 98), the rider, or an assistant, throws balls towards one or both of the conveyors 22, 24, whereby they will be moved relative to the dummy horse (which is itself moving at a simulated gallop), allowing the rider to hit the balls in a manner similar to that

experienced during a real polo match. Moreover, the motion of the horse more closely simulates a game of polo.

When it is desired to take a particular shot, one of the knee sensors 80a, 80b in combination with the lower sensor 84 on the neck portion 46 sense that the rider has assumed the correct posture for a particular shot and one of the indicator lights 94, 96 as appropriate (on the same side as the activated knee sensor 80a, 80b) illuminates in order to confirm this. By leaning to one side, the horse body 44 may be pivoted against the restoring force of the springs 70, 72, which again more closely simulates the action of a real polo pony.

The player then attempts to hit the ball and, if successful, hits one of the targets 36 which are provided with pressure sensors as described previously and which generate a signal whenever the sensor is hit. The counter 38 is arranged to keep a running total of "hits" on the targets.

If the ball is hit forwardly or to one side, it will rebound from the front or side wall 12, 14, 18 and move down the inclined walls 26, 28, 30 towards one of the conveyor belts 22, 24, where it becomes available for the rider to hit the ball again. This process is repeated until the balls collect at the junction at the rearmost portion of the conveyor belts and the rear inclined wall 32.

Thus, a rider may repeatedly hit a series of balls without having to dismount and without having to retrieve the balls once they have been hit. The simulated movement of the horse and the movement of the conveyors with respect to the horse also greatly enhance the realism, and therefore the effectiveness, of the practice. Moreover, by increasing the speed of the motor M the speed of the

TOP SECRET

12 13

16

17

18

34

galloping motion of the dummy horse is increased correspondingly with the speed of the conveyor belts 22, 24, whereby as the dummy horse “gallops” more quickly, its speed relative to a ball on the conveyor also increases in a manner similar to that which would be experienced on a real horse.

When it is desired to slow down the apparatus, the rider pulls on the reins 74, causing actuation of the microswitch 80 which sends a signal to the motor control unit 50 which causes the motor M to slow down, thereby slowing the movement of the body portion 44 and the conveyors 22, 24. Repeated actuation of the microswitch in this manner eventually causes the apparatus to stop.

The invention is not restricted to the details of the foregoing embodiment.